



Telecamera PTZ Dahua 4MP 30X IR HDCVI: la migliore soluzione di sorveglianza

Descrizione

Dahua 4MP 30X IR PTZ HDCVI

SD6C430I-HC-S2: IR speed dome HD-CVI da esterno/interno IP66 termoventilata, sensore CMOS progressivo 1/3" Sony Exmor, risoluzione 2K con 25Fps o 720p con 50Fps, rotazione PAN 360° endless (0.1°~160°/s) / TILT -15°~90° auto flip (0.1°~120°/s), ICR meccanico, modulo zoom Dahua da 30x (4.5~135mm f1.6~4.4) / 16x digitale, luminosità 0.05Lux f1.6 (0 con Led ON), led IR portata fino a 100mt, 1 uscita video (HD-CVI/CVBS), 2 ingressi e 1 uscite di allarme, 1 ingresso audio, OSD, 1 porta RS485, protocolli Pelco D/P e Dahua da 300 preset, 5 scan, 8 tour e 5 pattern, 2-3D, WDR (120db), home parking, programmatore orario, privacy mask 24 aree, alimentazione 24Vac <23W, alimentatore 24Vac/3A incluso

Model code	SD6C430I-HC
Chip Inch Size	1/3 inch
Colour Type	Colour / Monochrome
Resolution TVL	4MP
Dome Type	PTZ
Sensitivity lux	0 ~ 0.05 lux
Digital (DSP)	Yes

Indoor/Outdoor	Indoor/Outdoor
Electrical Specifications	Voltage: 24 V AC Power Consumption: 13W
Focal length	4.5 ~ 135 mm
Back Light Compensation	Yes
Auto Gain Control	Yes
White Balance	Yes
Electronic Shutter range	1/4s ~ 1/30,000s
S/ N (Signal/ Noise) Ratio dB	> 55
Signal Mode	PAL, NTSC
Built-in IR LED	Yes
Zoom Ratio	x30
Network Properties	Image Frame Rate: 25/30/50/60 fps
Physical Specifications	Dimensions mm: 205 x 336 Weight g: 5000
Environmental Specifications	Operating Temp °C: -40 ~ +60 C (-40 ~ +140 F) Operating Humidity %: <95 Protection: IP66
Additional info	• Powerful 30x optical zoom • 120dB true WDR, 3D DNR • Max. 25/30fps@4M/1080P, 25/30/50/60fps@720P • IR distance up to 100m • IP66

[Scarica scheda tecnica](#)

www.saisystem.it